



State when ordering  
 FW=.....mm  
 FH=.....mm  
 COW=.....mm  
 COH=.....mm  
 Cover  
 CL=.....mm

Profile option  
 Alt. F (concrete/brick)  
 Alt. U (aluminium/steel)

Surface treatment  
 Silver anodized  
 Special anodized.....  
 RAL.....  
 Special powder coating.....  
 .....

Glass  
 6/10/6 Insulated laminated glass

Lock  
 Floor lock Euro 1-way  
 Floor lock Euro 2-way

FW= Frame width  
 Min. 1000 / max. 2800  
 Alt. F FW=COW+7  
 Alt. U FW=COW+3

FH= Frame height  
 Min. 1900 / max. 3000

COW= Clear opening width  
 Alt. F COW=FW-7  
 Alt. U COW=FW-3

COH= Clear opening height  
 COH=FH

CL= Cover length

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

EntreMatic ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**Profile system**  
**EMPS-T Thermo with EMSL-T**  
**2 Panel wall mounted left**

**ENTRE MATIC**

2 833067