



State when ordering
 FW=.....mm
 FH=.....mm
 X=.....mm
 COW=.....mm
 COH=.....mm
 Cover
 CL=.....mm

Profile option
 Alt. F (concrete/brick)
 Alt. U (aluminium/steel)

Surface treatment
 Silver anodized
 Special anodized.....
 RAL.....
 Special powder coating.....

Glass
 8 mm laminated glass
 10 mm laminated glass
 12 mm laminated glass
 8 mm tempered glass
 10 mm tempered glass

Lock
 Floor lock Euro 1-way
 Floor lock Euro 2-way

FW= Frame width
 Min. 1600 / max. 4800
 Alt. F FW=3COW/2+33,5+X
 Alt. U FW=1,5COW+30,5+X

FH= Frame height
 Min. 1950 / max. 3000

X= Safety distance (50 mm)

COW= Clear opening width
 Alt. F COW=2(FW-33,5-X)/3
 Alt. U COW=2(FW-33,5-X)/3+2

COH= Clear opening height
 COH=FH-50

CL= Cover length Scale 1:5

Customer: _____
 Door id: _____
 Project No: _____

EntreMatic ref: _____
 Date: _____
 Sign: _____

**Profile system
 EMPS-T with EMSL-T
 3 Panel wall mounted right**

ENTRE MATIC

2 833062